

APPLICATION:
LOW ENERGY OPERATOR
RIGHT HAND CENTER PIVOT

NOTE: DRAWING IS DIMENSIONED IN BOTH INCHES & METRIC (mm)
AUTOMATIC SWING DOOR OPERATOR SHALL BE "FA8" CETL USA
APPROVED, CONFORMING TO UL STD. 325 & ANSI-BHMA STD. A156.19
FIRE RATED TO UL STD. 10(B); UL STD. 10(C), CERTIFIED TO CAN.
CSA STD. C22.2#247 AS MANUFACTURED BY RECORDED-USA.
32" (813) CLEAR OPENING REQUIRED TO MEET ADA REQUIREMENT.

STANDARD FINISH: ANODIZED, CLEAR; DARK BRONZE;
SPECIAL FINISHES ARE AVAILABLE

120V AC. 60HZ. 15A.
BY ELEC. CONTRACTOR.

CONTROLS

HA8 HEADER

SWING HOLLOW
METAL, ALUMINUM
OR WOOD DOORS
AND FRAMES BY
OTHERS

AUTOMATIC
CAUTION
DOOR

BOTTOM PIVOT
BY OTHERS

FIN. FLOOR

ELEVATION

REINFORCEMENT
BY OTHERS

DRYWALL BY
OTHERS

HA8
OPERATOR
& HEADER

4 1/2"
(114.3)

NOTE:
HINGE SIDE
TOP RAIL
NEEDS CUT
OUT ON BACK
OF DOOR FOR
OPERATOR ARM
(MIN 1 5/8" x
DEPTH OF WEB)
(41.3)

VERTICAL
SECTION

6 1/2"
(165.1)

5/8"
(15.9)

INTERIOR
PLAN

CLEARANCE HOLES
1/4" (6.4) FLAT HEAD
SCREWS.

HA8 CENTER PIVOT ARM

HEADER TO BE SIZE OF FRAME OPENING

LOCK CYLINDER

2 3/4" C/L PIVOT
(69.9)

INTERIOR

HORIZONTAL SECTION



TEL. 877-348-6837 (CANADA)
TEL. 833-921-1337 (USA)
www.recorddoors.com

JOB NAME:

LOCATION:

DOOR NUMBER:

SHEET NO.

7

SECTION

HA