

**Alubrand outside sliding door system R12**

**Front view from Outside (Front view)**

**Front view from Inside (Side view)**

**Top view**

**Side view**

**Technical specifications:**

- Material: Anodized Aluminium
- Color: RAL 9006 (White)
- Thickness: 2,0 mm
- Weight: 12,5 kg/m²
- Wind load: 1,0 kN/m²
- Water resistance: 120 min.
- Sound insulation: 30 dB
- Fire resistance: 30 min.
- Security: 30 min.
- Temperature range: -20°C to +50°C
- UV radiation: 10000 h
- Corrosion resistance: 1000 h
- Lead time: 4-6 weeks

**Accessories:**

- Handrail
- Door stop
- Door pull
- Door lock
- Door handle
- Door knob
- Door lock cylinder
- Door lock handle
- Door lock knob
- Door lock cylinder handle
- Door lock cylinder knob
- Door lock cylinder handle knob
- Door lock cylinder handle knob

**Dimensions:**

Width	1200
Height	2000
Depth	100

**Alubrand outside sliding door system R12**

**Front view from Outside (Front view)**

**Front view from Inside (Side view)**

**Technical specifications:**

- Material: Anodized Aluminium
- Color: RAL 9006 (White)
- Thickness: 2,0 mm
- Weight: 12,5 kg/m²
- Wind load: 1,0 kN/m²
- Water resistance: 120 min.
- Sound insulation: 30 dB
- Fire resistance: 30 min.
- Security: 30 min.
- Temperature range: -20°C to +50°C
- UV radiation: 10000 h
- Corrosion resistance: 1000 h
- Lead time: 4-6 weeks

**Accessories:**

- Handrail
- Door stop
- Door pull
- Door lock
- Door handle
- Door knob
- Door lock cylinder
- Door lock handle
- Door lock knob
- Door lock cylinder handle
- Door lock cylinder knob
- Door lock cylinder handle knob
- Door lock cylinder handle knob
- Door lock cylinder handle knob

**Dimensions:**

Width	1200
Height	2000
Depth	100