



Record Impression Speedgate

Shape positive impressions in your highest traffic areas

Impress your visitors with flexible, elegant and sophisticated speedgates from Record.

We encounter too few opportunities to shape aesthetic appreciation in the pursuit of functional goals. That changes with the Record Impression Speedgate. This innovative access control solution benefits from streamlined design, thoughtful accents and finish options, as well as seamless integration with access control technologies. The result turns high flow passage into an opportunity to move.

The flexible constructs and attentive detailing of the Record Impression Speedgate creates new possibilities to impress: with its modular design ensuring that it can be installed as a single or multi-lane array (or even combined with a wide-lane setup), this speedgate is fully capable of integrating perfectly with any architectural style, as well as enabling access to all types of visitors.

Equipped with high processing capacity and an advanced detection system, the Impression Speedgate guarantees accurate user tracking and can reliably detect jump-overs and tailgating. Coupled with its wide range of color and material options, the Impression Speedgate supports functional purpose with true style.

What makes the Impression Speedgate stand out?

LED bands for intuitive user guidance

Three cabinet design options
(Open, Boxed or Center Glass)

Pick and choose colors to match
your environment

Seamless integration of access control system
technologies and biometrics

Safe and secure operation with advanced
sensor technology

Energy-efficient and sustainable performance

Accessible for wheelchair users and people
with strollers

Accessories

- » Top mounting integration options
- » Face recognition integration
- » Ramp for finished floor installations

Options

Cabinet design: Open, Boxed or Center Glass
Cabinet lengths: 47.25" (1200 mm), 57.06" (1450 mm), 67" (1700 mm)
Surface treatment: RAL
Inlay: RAL or customized

Technical specifications

Power supply	110–240 VAC, 50 / 60 Hz
Auxiliary voltage	24 VDC
Operating temperature	32°F to 122°F (+0°C to +50°C)
Passageway width	23.62" (600 mm) to 43.31" (1100 mm)
Wing heights	39.37" (1000 mm) 47.25" (1200 mm) 70.86" (1800 mm)
Cabinet width	4.437" (112.7 mm)
Minimum opening/closing time	0.7 sec (depending on passageway width)
Noise level	55 dB at 1 m distance
IP Protection	IP40 (conforming with EU standards)

Flow is in the details

The Impression Speedgate was designed to make the people flow experience as organic as possible. From the audiovisual feedback to the multiple passageway width options, this speedgate is designed for anyone and everyone.



Sustainable by nature

Technology at its best: the Impression Speedgate switches into sleep mode when people flow has stopped for a short time. Minimal energy consumption – maximum sustainability for your environment.



This equipment should be installed, regularly inspected, maintained and serviced by trained and authorized personnel. Preventive maintenance plans are highly recommended for proper and safe operation.

Flexible options, full solutions

*Frosted glass not offered, shown for illustration.

Open	Center Glass	Boxed