

**record-usa**4324 PHIL HARGETT CT.
MONROE, NC 28110
(704) 289 - 9212


JOB NAME: _____

LOCATION: _____


SERIES 5100 AUTOMATIC SLIDING DOORS

TYPE: 5104-1, SO-SX, L.H. SINGLE


PAGE 51-2.04

**ELEVATION VIEW**


SCALE: 1/4" = 1'0"

**PLAN VIEW**

SCALE: 1/4" = 1'0"

**SECTION: 1**

SCALE: 1/4 SIZE

**SECTION: 2**

SCALE: 1/4 SIZE

NOTES:

1. See sheets 51-2.86 thru 51-2.91 for optional muntins, bottom rails, transoms, glazing variations, bottom guides & thresholds.
2. See sheet 51-2.92 for additional details of recessed pin guide.

DIMENSIONS FOR STANDARD NARROW STILE PACKAGES

DOOR OPENING "A"	STD. PACKAGE WIDTH "B"	STD. PACKAGE HEIGHT "C"	DOOR OPENING HEIGHT W/THRESHOLD	DOOR OPENING HEIGHT W/O THRESHOLD	MAX OPENING MANUALLY
35-3/8 (899)	84 (2134)	91 (2311)	82-3/4 (2102)	83-1/4 (2115)	75-1/16 (1907)
41-3/8 (1051)	96 (2438)	91 (2311)	82-3/4 (2102)	83-1/4 (2115)	87-1/16 (2211)
44-3/8 (1127)	102 (2591)	91 (2311)	82-3/4 (2102)	83-1/4 (2115)	93-1/16 (2364)
47-3/8 (1203)	108 (2743)	91 (2311)	82-3/4 (2102)	83-1/4 (2115)	99-1/16 (2516)

Masonry opening is 1/4" (6) per side larger and 1/4" taller than package dimensions. Measurements given in inches (millimeters).